



FLUORESCENT BALLAST

J1/20TS120-TP

ELECTRICAL CHARACTERISTICS

No. Lamps	Lamp Type	Nominal Lamp Watts	Line Voltage	Hertz	Line Current (Amps)	Ballast Type	Min. Start Temp.	Sound Rating
1	F14T12 F15T8 F15T12 F20T12	14W 15W or 20W	120V	60Hz	0.625A	LPF TS	50°F	A

PHYSICAL CHARACTERISTICS


Overall Dimensions			Mounting Dimensions		Lead Lengths			
Length	Width	Height	Length	Width	Black	White	Blue	Red
6 ½"	1 7/8"	1 5/12"	6 1/6"	1 7/8"	12"	19"	20"	16" x 16"

PACKAGING INFORMATION

Units/ Carton	Weight/ Carton	Cube/ Carton	Quantity/ Pallet	Weight/ Pallet	Cube/ Pallet
30 pcs.	61 lbs.	0.40 ft.	780 pcs.	1,649 lbs.	19.3 ft.

CERTIFICATIONS

UL	CSA	CBM	cUL	E
✓			✓	



Certifications:
UL File No. E172098

Ordering Information:

J ▶	JADCO Compact Fluorescent Ballast
1 ▶	Primary Lamp Count Design
20 ▶	Primary Lamp Type
TS ▶	Ballast Type - Trigger Start
120 ▶	Input Line Voltage
TP ▶	Thermally Protected