



FLUORESCENT BALLAST

J1/40RS120ES-TP

ELECTRICAL CHARACTERISTICS

No. Lamps	Lamp Type	Nominal Lamp Watts	Line Voltage	Hertz	Line Current (Amps)	Ballast Type	Min. Start Temp.	Sound Rating
1	F40T12	34W or 40W	120V	60Hz	0.43A	HPF RS	40W 50°F 34W 60°F	A

PHYSICAL CHARACTERISTICS


Overall Dimensions			Mounting Dimensions			Lead Lengths		
Length	Width	Height	Length	Width	Black	White	Blue	Red
9 ½"	2 2/5"	1 5/8"	8 7/8"	2 2/5"	22"	22"	26" x 26"	34" x 34"

PACKAGING INFORMATION

Units/Carton	Weight/Carton	Cube/Carton	Quantity/Pallet	Weight/Pallet	Cube/Pallet
10 pcs.	34.25 lbs.	0.31 ft.	540 pcs.	2,101 lbs.	23.3 ft.

CERTIFICATIONS

UL	CSA	CBM	cUL	E
✓	✓			✓



Certifications:
UL File No. E172098



Ordering Information:

J ▶	JADCO Fluorescent Ballast
1 ▶	Primary Lamp Count Design
40 ▶	Primary Lamp Type
RS ▶	Ballast Type - Rapid Start
120 ▶	Input Line Voltage
ES ▶	Energy Saving
TP ▶	Thermally Protected