




SERVICE ENTRANCE HEAD: CLAMP-ON-TYPE



SPECIFICATIONS

- Clamp-on type head used with rigid conduit, IMC or EMT for pulling service drops conductors.
- Assembled with electrical grade phenolic insulator with multiple holes.
- UL listed and CSA certified for use in wet locations.
- Cast from high strength, corrosion and weather resistant aluminum alloy.

PACKING INFORMATION

Model Number	Trade Size	Inner Ctn. Packing	Inner Ctn. Weight	Outer Ctn. Packing	Outer Ctn. Weight	Insulator Hole Size	No. of Holes
JCO-1	½"	10	2.27	50	11.32	19/64	4
JCO-2	¾"	10	2.70	50	13.51	3/8 13/32	2 3
JCO-3	1"	5	1.69	25	8.44	7/16 1/2	2 3
JCO-4	1¼"	5	2.50	25	12.46	27/64 5/8	2 3
JCO-5	1½"	3	2.02	15	10.07	19/32 7/16 ¾	2 1 3
JCO-6	2"	--	--	5	5.54	17/32 ¾ 1	1 2 3
JCO-7	2½"	--	--	1	3.94	7/8 1 1-5/16	3 1 3
JCO-8	3"	--	--	1	4.13	7/8 1 1-5/16	3 1 3
JCO-9	3½"	--	--	1	6.22	1-1/8 1-3/4	4 3
JCO-10	4"	--	--	1	6.33	1-1/8 1-3/4	4 3



Certifications:
UL File No. E121488
CSA File No. LR57925

