




SERVICE ENTRANCE HEAD: THREADED TYPE



SPECIFICATIONS

- Threaded type head used with threaded rigid conduit and IMC for pulling service drop conductors.
- Assembled with electrical grade phenolic insulator with multiple holes.
- UL listed and CSA certified for use in wet locations.
- Cast from high strength, corrosion and weather resistant aluminum alloy.

PACKING INFORMATION

Model Number	Trade Size	Inner Ctn. Packing	Inner Ctn. Weight	Outer Ctn. Packing	Outer Ctn. Weight	Insulator Hole Size	No. of Holes
JTH-1	½"	5	1.09	50	10.89	19/64	4
JTH-2	¾"	5	0.99	25	4.92	3/8 13/32	2 3
JTH-3	1"	--	--	10	2.95	7/16 1/2	2 3
JTH-4	1¼"	--	--	10	3.87	27/64 5/8	2 3
JTH-5	1½"	--	--	10	6.97	19/32 7/16 ¾	2 1 3
JTH-6	2"	--	--	5	5.44	17/32 ¾ 1	1 2 3
JTH-7	2½"	--	--	2	7.38	7/8 1 1-5/16	3 1 3
JTH-8	3"	--	--	1	3.69	7/8 1 1-5/16	3 1 3
JTH-9	3½"	--	--	1	7.22	1-1/8 1-3/4	4 3
JTH-10	4"	--	--	1	6.10	1-1/8 1-3/4	2 4



Certifications:
UL File No. E121488
CSA File No. LR57925

