




ZINC CONDUIT BUSHINGS



SPECIFICATIONS

- Used with locknut to terminate threaded rigid conduit or IMC to enclosure.
- Bushing surface rounded to prevent damage to wire insulation during pulling.
- Available with or without insulator
- Insulated version has 150°C rated Nylon insulator.
- Die cast from high strength zinc alloy.

PACKING INFORMATION - without Insulator

Model Number	Trade Size	Inner Ctn. Packing	Inner Ctn. Weight	Outer Ctn. Packing	Outer Ctn. Weight
JGB-1	½"	100	2.20	1000	22.00
JGB-2	¾"	100	2.50	1000	25.00
JGB-3	1"	50	2.25	500	22.50
JGB-4	1 ¼"	25	1.95	250	19.50
JGB-5	1 ½"	25	2.13	250	21.25
JGB-6	2"	25	2.70	250	27.00
JGB-7	2 ½"	10	2.78	100	27.80
JGB-8	3"	10	3.42	100	34.20
JGB-9	3 ½"	5	1.96	50	19.60
JGB-10	4"	5	2.26	50	22.55

PACKING INFORMATION - with Insulator

Model Number	Trade Size	Inner Ctn. Packing	Inner Ctn. Weight	Outer Ctn. Packing	Outer Ctn. Weight
JGBI-1	½"	100	2.50	1000	25.00
JGBI-2	¾"	100	2.70	1000	27.00
JGBI-3	1"	50	2.40	500	24.00
JGBI-4	1 ¼"	25	2.05	250	20.50
JGBI-5	1 ½"	25	2.20	250	22.00
JGBI-6	2"	25	2.80	250	28.00
JGBI-7	2 ½"	10	2.84	100	28.40
JGBI-8	3"	10	3.47	100	34.70
JGBI-9	3 ½"	5	20.4	50	20.35
JGBI-10	4"	5	2.33	50	23.30



Certifications:
UL File No. E155411
CSA File No. LR57925

