




ZINC WATER TIGHT HUBS



SPECIFICATIONS

- Used to terminate threaded rigid conduit or IMC to enclosure.
- Assembled with 105°C rated throat insulator and BUNA-N sealing ring.
- UL listed and CSA certified for use in wet locations.
- Meets NEMA sealing requirements for Type 2, 3, 3R, 4, 5, 12, and 13 enclosures.
- Certified for use in hazardous locations, Class II, Groups E, F, G and Class III.
- Die cast from high strength zinc alloy.

PACKING INFORMATION

Model Number	Trade Size	Inner Ctn. Packing	Inner Ctn. Weight	Outer Ctn. Packing	Outer Ctn. Weight
JWH-1	½"	20	3.82	100	19.10
JWH-2	¾"	20	5.22	100	26.10
JWH-3	1"	20	8.00	100	40.00
JWH-4	1¼"	10	5.27	50	26.35
JWH-5	1½"	10	7.25	50	36.25
JWH-6	2"	5	4.73	25	23.63
JWH-7	2½"	--	--	10	17.50
JWH-8	3"	--	--	5	11.00
JWH-9	3½"	--	--	5	13.13
JWH-10	4"	--	--	5	13.75

Certifications:

UL File No. E155411
 CSA File No. LR57925
 NEMA Type 2, 3, 3R, 4, 5, 12 & 13
 Hazardous Locations
 Class I, Div. 2
 Class II, Div. 1 (Groups E, F, G), Div. 2
 Class III, Div. 1 & 2

