




ZINC STRAIGHT SQUEEZE CONNECTORS



SPECIFICATIONS

- Used with locknut to terminate steel or aluminum flexible metal conduit and armored cable to enclosure.
- Assembled with die cast locknut and tri-combo screws.
- Die cast from high strength zinc alloy.

PACKING INFORMATION

| Model Number | Trade Size | Inner Ctn. Packing | Inner Ctn. Weight | Outer Ctn. Packing | Outer Ctn. Weight |
|----------------|------------|--------------------|-------------------|--------------------|-------------------|
| JSSQ-0 | 3/8" | 50 | 2.90 | 500 | 29.00 |
| JSSQ-1 | 1/2" | 25 | 2.00 | 250 | 20.00 |
| JSSQ-2 | 3/4" | 25 | 2.67 | 250 | 26.65 |
| JSSQ-3 | 1" | 10 | 2.00 | 100 | 20.00 |
| JSSQ-4 | 1 1/4" | 10 | 2.72 | 100 | 27.20 |
| JSSQ-5 | 1 1/2" | 5 | 1.61 | 50 | 16.10 |
| JSSQ-6 | 2" | 10 | 4.46 | 50 | 17.84 |
| JSSQ-7 | 2 1/2" | 1 | 0.90 | 5 | 4.50 |
| JSSQ-8 | 3" | 1 | 1.27 | 5 | 6.35 |
| JSSQ-9 | 3 1/2" | -- | -- | 1 | 0.97 |
| JSSQ-10 | 4" | -- | -- | 1 | 2.10 |



Certifications:
UL File No. 155411
CSA File No. LR57925

