




ZINC STRAIGHT LIQUID TIGHT CONNECTORS



SPECIFICATIONS

- Used with locknut to terminate liquid tight flexible metal conduit and Type B non-metallic conduit to enclosure.
- Assembled with die cast zinc locknut.
- Available with or without 105°C rated insulator.
- Die cast from high strength zinc alloy.

PACKING INFORMATION - without Insulator

Model Number	Trade Size	Inner Ctn. Packing	Inner Ctn. Weight	Outer Ctn. Packing	Outer Ctn. Weight
JSLT-0	3/8"	25	4.16	100	16.65
JSLT-1	1/2"	25	3.43	100	13.70
JSLT-2	3/4"	10	2.00	100	20.00
JSLT-3	1"	5	1.70	25	8.50
JSLT-4	1 1/4"	5	2.81	25	14.05
JSLT-5	1 1/2"	2	1.28	10	6.40
JSLT-6	2"	2	1.72	10	8.61

PACKING INFORMATION - with Insulator

Model Number	Trade Size	Inner Ctn. Packing	Inner Ctn. Weight	Outer Ctn. Packing	Outer Ctn. Weight
JSLT-7	2 1/2"	1	2.07	5	10.36
JSLT-8	3"	--	--	1	2.80
JSLT-9	3 1/2"	--	--	1	3.22
JSLT-10	4"	--	--	1	3.65



Certifications:
UL File No. E155411
CSA File No. LR57925

