



## EMERGENCY LIGHT (FIXED HEADS)



### ELECTRICAL CHARACTERISTICS

Model #	Housing	Heads	Lamp Type	Lamp V DC	Lamp Watts
<b>JSE-80</b>	Thermoplastic	Fixed Heads	T-5 Incandescent	6	2 x 5.4

### PACKING INFORMATION

Units Per Carton	Weight Per Unit	Cube Unit
1 pc.	3.7 lbs.	0.13 cu.

### Construction & Application

<b>Description:</b>	The JSE-80 is an attractive, economical alternative to traditional double headed emergency lighting fixtures. It has an aesthetically appealing low profile and is quick and simple to install.
<b>Application:</b>	Suitable for use in almost any commercial or light industrial application.
<b>Options:</b>	UL damp location listing. Halogen lamps.
<b>Approvals:</b>	UL924. UL Listed for damp locations. Life Safety NFPA 101.
<b>Housing:</b>	The housing is made of injection molded thermoplastic. It has high impact resistance and is UL94-5V rated.
<b>Mounting:</b>	The back mounting plate is made of injection molded thermoplastic. It has a molded in universal J-Box mounting pattern and keyhole slots. The main housing snaps on to the back plate for quick and easy installation.
<b>Lens:</b>	Computer designed optical prisms throw the light outward and to the sides for maximum utilization.
<b>Electrical / Battery:</b>	<ul style="list-style-type: none"> <li>• Dual voltage input 120/277 VAC, 60 Hz.</li> <li>• Maintenance free, Sealed Lead Calcium 6V, 4.2 AH battery with a maximum full recharge time of 48 hours. Minimum 1 ½ hour emergency operation.</li> <li>• Low voltage disconnect of the battery prevents deep discharge and maintains good battery life.</li> <li>• Fully automatic, solid state charger.</li> <li>• Test switch with LED charge indicator/AC voltage indicator.</li> <li>• Line latching feature prevents the unit from turning on during installation to a non-energized AC circuit. Saves labor since the installer does not have to return to connect the battery terminals once the building is energized.</li> </ul>