



MEDIUM FLOODLIGHT (WIRED)



CONSTRUCTION

- Die Cast Housing / Chromate Conversion Coating
- 1/2" NPS Knuckle Assembly
- Textured Bronze Finish
- Hinged High Impact Tempered Glass Lens / Aluminum Reflector
- Includes Medium Base Socket
- External Accessibility Compartment
- Ballast Mounting Bracket
- Includes Ballast and Lamp as Shown

APPLICATION

- Accent, Perimeter, Security Lighting
- Ideal for Signage, Façade, and Landscape
- General Purpose Commercial and Industrial Floodlight

ELECTRICAL CHARACTERISTICS

Model #	Voltage	Wattage	Hertz	Lamp Type	Ballast Type
JFL70HPS120M-PK	120V	70W	60Hz	HPS	REACTOR-NPF
JFL100HPS120M-PK	120V	100W	60Hz	HPS	REACTOR-NPF
JFL150HPS120M-PK	120V	150W	60Hz	HPS	REACTOR-NPF
JFL70MHQVM-PK	Quad	70W	60Hz	MH	HX-HPF
JFL100MHQVM-PK	Quad	100W	60Hz	MH	HX-HPF
JFL150MHQVM-PK	Quad	150W	60Hz	MH	HX-HPF
JFL175MHQVM-PK	Quad	175W	60Hz	MH	CWA-HPF

JFL70HPS220/50M-PK	120/220/240V	70W	50Hz	HPS	REACTOR-NPF
JFL100HPS220/50M-PK	120/220/240V	100W	50Hz	HPS	REACTOR-NPF
JFL150HPS220/50M-PK	120/220/240V	150W	50Hz	HPS	REACTOR-NPF
JFL70MH220/50M-PK	120/220/240V	70W	50Hz	MH	HX-HPF
JFL100MH220/50M-PK	120/220/240V	100W	50Hz	MH	HX-HPF
JFL150MH220/50M-PK	120/220/240V	150W	50Hz	MH	CWA-HPF

PRODUCT DIMENSIONS

Width	Height	Depth
9"	10 1/4"	7 1/4"

