



SMALL FLOODLIGHT (WIRED)



CONSTRUCTION

- Die Cast Housing
- ½" NPS Knuckle Assembly
- Hinged High Impact Tempered Glass Lens
- Includes porcelain medium base socket
- Ballast and Lamp Included as Shown

APPLICATION

- Accent, Perimeter, Security Lighting
- Ideal for Signage, Façade, and Landscape Lighting
- General Purpose Commercial and Industrial Floodlight

ELECTRICAL CHARACTERISTICS

Model #	Voltage	Wattage	Hertz	Lamp Type	Ballast Type
JFL35HPS120-PK	120V	35W	60Hz	HPS	REACTOR-NPF
JFL50HPS120-PK	120V	50W	60Hz	HPS	REACTOR-NPF
JFL70HPS120-PK	120V	70W	60Hz	HPS	REACTOR-NPF
JFL100HPS120-PK	120V	100W	60Hz	HPS	REACTOR-NPF
JFL150HPS120-PK	120V	150W	60Hz	HPS	REACTOR-NPF
JFL70HPS220/50-PK	120/220/240V	70W	50Hz	HPS	REACTOR-NPF
JFL100HPS220/50-PK	120/220/240V	100W	50Hz	HPS	REACTOR-NPF
JFL150HPS220/50-PK	120/220/240V	150W	50Hz	HPS	REACTOR-NPF

PRODUCT DIMENSIONS

Width	Height	Depth
9"	7 ½"	6"

