



6" WRAP FIXTURE (WIRED)



CONSTRUCTION

- Housing & End Cap: CRS 0.4mm White Powder Coated
- Ballast Channel: CRS 0.5mm White Powder Coated
- Diffuser: #12 Acrylic Prismatic Lens, 1~2.5mm thick
- Surface mounting
- Packaging size: 50-3/8" x 7-7/8" x 3-3/16"
- UL, cUL listed

ELECTRICAL CHARACTERISTICS

Model #	Wattage	Voltage	Ballast Type	Power Factor
J6WRAP2/40RS120LPF-TP	2 x 40W	120V	Magnetic	LPF
J6WRAP2/32IS120LPF-TP	2 x 32W	120V 50/60Hz	Electronic	LPF

PRODUCT DIMENSIONS

Model #	Length	Width	Height
J6WRAP2/40RS120LPF-TP	48 3/4"	6 1/2"	2 3/4"
J6WRAP2/32IS120LPF-TP	48 3/4"	6 1/2"	2 3/4"

PACKING INFORMATION

Model#	Pcs/Ctn	Weight/Ctn	Cube/Ctn
J6WRAP2/40RS120LPF-TP	1 pc.	9.24 lbs.	0.95
J6WRAP2/32IS120LPF-TP	1 pc.	7.48 lbs.	0.95

