



9" WRAP FIXTURE (WIRED)



CONSTRUCTION

- Housing & End Cap: CRS 0.7mm White Powder Coated
- Ballast Channel: CRS 0.5mm White Powder Coated
- Diffuser: Acrylic Prismatic lens bottom and linear side reflector
- Low Profile, Surface mounting
- Self-Centering Lens is supported the entire length, and can be hinged down from either side for easy maintenance
- Packaging size: 49-3/4" x 9-3/4" x 3-1/2"
- UL, cUL listed

ELECTRICAL CHARACTERISTICS

Model #	Wattage	Voltage	Ballast Type	Power Factor
J9WRAP2/40RSI20LPF-TP	2 x 40W	120V	Magnetic	LPF
J9WRAP2/32ISI20LPF-TP	2 x 32W	120V 50/60Hz	Electronic	LPF
J9WRAP2/17ISI20LPF-TP	2 x 17W	120V 50/60Hz	Electronic	LPF

PRODUCT DIMENSIONS

Model #	Length	Width	Height
J9WRAP2/40RSI20LPF-TP	48"	9"	3"
J9WRAP2/32ISI20LPF-TP	48"	9"	3"
J9WRAP2/17ISI20LPF-TP	24"	9"	3"

PACKING INFORMATION

Model#	Pcs/Ctn	Weight/Ctn	Cube/Ctn
J9WRAP2/40RSI20LPF-TP	1 pc.	14.41 lbs.	0.930
J9WRAP2/32ISI20LPF-TP	1 pc.	12.19 lbs.	0.930
J9WRAP2/17ISI20LPF-TP	1 pc.	12.19 lbs.	0.375

