



9" WRAP FIXTURE (WIRED)

ELECTRICAL CHARACTERISTICS

Model #	Wattage	Voltage	Ballast Type	Power Factor
J9WRAP2/40RS120LPF-TP	2 x 40W	120V	Magnetic	LPF
J9WRAP2/32-40RS120LPF-TP	2 x 32-40W	120V 50/60Hz	Electronic	LPF
J9WRAP2/17-20IS120LPF-TP	2 x 17-20W	120V 50/60Hz	Electronic	LPF

PRODUCT DIMENSIONS

Model #	Length	Width	Height
J9WRAP2/40RS120LPF-TP	48 "	9"	3"
J9WRAP2/32-40RS120LPF-TP	48"	9"	3"
J9WRAP2/17-20IS120LPF-TP	24"	9"	3"

PACKING INFORMATION

Model#	Pcs/Ctn	Weight/Ctn	Cube/Ctn
J9WRAP2/40RS120LPF-TP	1 pc.	13.7 lbs.	0.99
J9WRAP2/32-40RS120LPF-TP	1 pc.	12.2 lbs.	0.99
J9WRAP2/17-20IS120LPF-TP	1 pc.	6.7 lbs.	0.50

CONSTRUCTION

- Housing & End Cap: CRS 0.7mm White Powder Coated
- Ballast Channel: CRS 0.5mm White Powder Coated
- Diffuser: Acrylic Prismatic Lens bottom and linear side reflector
- Low Profile, Surface mounting
- Self-Centering Lens is supported the entire length, and can be hinged down from either side for easy maintenance
- Packaging size for 4FT Model: 49-3/4" x 9-3/4" x 3-1/2"
- Packaging size for 2FT Model: 25-3/4" x 9-3/4" x 3-1/2"
- UL, cUL listed

