



# DECORATOR VENTED BATH FANS

## ELECTRICAL CHARACTERISTICS

Model#	Airflow / Sound	Duct / Watts	Finish
<b>JBFV50LMG/SS</b>	50 CFM / 57dB	4" / 2x60W	Stainless Steel
<b>JBFV70LMG/SS</b>	70 CFM / 57dB	4" / 2x60W	Stainless Steel

## PACKING INFORMATION

Model#	Units Per Carton	Weight Per Carton	Cube Per Carton
<b>JBFV50LMG/SS</b>	1 pc.	3.8 lbs.	1.47
<b>JBFV70LMG/SS</b>	1 pc.	5.0 lbs.	1.47

## CONSTRUCTION

- Galvanized Housing resists humid conditions and changing attic temperatures, unlike plain steel housing used in many vents
- Housing has ceiling/wall thickness indicator markings and built-in mounting tabs for quick installation
- Precision stamped grille with 360° of air openings and white powder paint finish
- Molded designer frosted glass globe
- Easy remove and install motor assembly with keyhole mounting bracket
- Permanently lubricated motor with plug for quick activations
- Built-in junction box for easy wiring
- Molded Fan Blade—precision balanced for quiet operation
- Molded duct adaptor with built-in damper
- Incandescent models have twin medium base lampholders, maximum 60W each (lamps not included)
- Fluorescent model includes twin 13W PL sockets and ballasts
- Units and service parts are CSA listed

## PRODUCT DIMENSIONS

