



## COMPACT FLUORESCENT MEDIUM FLOODLIGHT

Model #	Wattage	Voltage	Hertz	Ballast	Base	Lumens
<b>JFL2/42CFLMVM-PK</b>	2 X 42W 4-Pin CFL	120-277V	50/60Hz	Electronic	GX24q4	6400

### PRODUCT DIMENSIONS

Width	Height	Depth
9"	10-1/4"	7-1/4"

### PACKING INFORMATION

Pcs/Ctn	Weight/Ctn	Cube/Ctn
1 pc.	2.5 lbs.	0.41 cft.

### APPLICATIONS & FEATURES

#### APPLICATIONS:

- Accent, Perimeter, Security Lighting
- Ideal for Signage, Façade, and Landscape Lighting
- General Purpose Commercial and Industrial Flood

#### FEATURES:

- Die Cast Aluminum Housing and Hinged Top Frame
- Textured Architectural Bronze Powder Coat Finish Over a Chromate Conversion Coating
- Aluminum Reflector
- Tempered Glass Lens
- Plug-In Type GX24Q-4 Base
- Adjustable Knuckle with Angle Indicators and 1/2" NPT Threads
- 1 x 26W to 42W, 2 x 26W to 42W CFL Bulb
- CSA Listed for Wet Locations

