



## PARABOLIC TROFFER BODIES (WIRED)



**2 x 2**



**2 x 4**

Model #	Size	Wattage	Voltage	Description
<b>JPT22-2/32UISMV/9CELL</b>	2 x 2	2x32W T8 U-Tubes or 2x40W T12 U-Tubes	120-277V	9 Cell (4-T8 Sockets Included)
<b>JPT24-3/32ISMV/18CELL</b>	2 x 4	3x32W T8 or 3x40W T12	120-277V	18 Cell (6-T8 Sockets Included)

### PRODUCT DIMENSIONS

Model #	Length	Width	Height
<b>JPT22-2/32UISMV/9CELL</b>	24.4"	24.6"	6.2"
<b>JPT24-3/32ISMV/18CELL</b>	48.6"	24.8"	6.2"

### PACKING INFORMATION

Model #	Pcs/Ctn	Weight/Ctn	Cube/Ctn
<b>JPT22-2/32UISMV/9CELL</b>	1 pc.	19.84 lbs.	2.15 cft.
<b>JPT24-3/32ISMV/18CELL</b>	1 pc.	25.56 lbs.	4.32 cft.

### FEATURES AND APPLICATIONS

- High Performance
- T8 Luminaire Provides General Illumination for Recessed Applications
- Innovative Low-Profile Design Optimized around T8 Lamps, Low Profile Electronic Ballasts and T8 Compact Sockets
- Integral T-bar Safety Clips are Standard—no need to install separate clips
- UL Approved