



COMPACT FLUORESCENT BRAVO! EURO-STYLE WALL PACK

Model #	Wattage	Voltage	Hertz	Ballast	Base	Lumens
JWB2/42CFLMV-PK	2 X 42W 4-Pin CFL	120-277V	50/60Hz	Electronic	GX24q4	6400
PRODUCT DIMENSIONS						
Width		Height		Depth		
10-3/8"		12-1/4"		7-3/8"		
PACKING INFORMATION						
Pcs/Ctn		Weight/Ctn		Cube/Ctn		
1 pc.		3.7 lbs.		1.14 cft.		
APPLICATIONS & FEATURES						

APPLICATIONS:

- Ideal for Security and Perimeter Lighting
- For Warehouse, Schools, and Loading Docks
- Commercial, Industrial, and Institutional Lighting

FEATURES:

- Die-Cast Aluminum back housing with Cast-In Template for Mounting Over and Electrical box, Color matched Polycarbonate Front Housing with Clear Ribbed Lens Area, 1/2" Coin Plugs with O-Rings for Conduit and Photocell, Textured Architectural Bronze Powder Coat Finish over a Chromate Conversion Coating
- Aluminum Reflector
- Clear Ribbed Polycarbonate Lens in Front Housing
- Plug-in Type Socket, GX24Q-4
- Mount Over 4" Recessed Outlet Box or Use 1/2" Surface Conduit
- 1 x 26W to 42W, 2 x 26W to 42W CFL
- CSA Listed for Wet Locations

