



COMPACT FLUORESCENT SMALL WALL LIGHT

Model #	Wattage	Voltage	Hertz	Ballast	Base	Lumens
JWL2/42CFLMV-PK	2 X 42W 4-Pin CFL	120-277V	50/60 Hz	Electronic	GX24q4	6400
PRODUCT DIMENSIONS						
Width		Height		Depth		
5-1/4"		11"		6-3/4"		
PACKING INFORMATION						
Pcs/Ctn		Weight/Ctn		Cube/Ctn		
1 pc.		3.0 lbs.		0.45 cft.		
APPLICATIONS & FEATURES						

APPLICATIONS:

- Ideal for Security and Perimeter Lighting
- For Warehouses, Schools, and Loading Docks
- Commercial, Industrial, and Institutional Lighting

FEATURES:

- Die Cast Aluminum Housing, Textured Bronze Finish over a Chromate Conversion Coating with Conduit Access on Bottom and Back
- Aluminum Reflector
- Molded Prismatic Borosilicate Glass Lens
- Plug-in Type Socket, GX24Q4
- Optional Cast Aluminum Mounting Plate Mounts Directly Over a 4" Recessed Outlet Box
- 1 x 26w to 42W, 2 x 26W to 42W CFL
- CSA Listed for Wet Locations

