



COMPACT FLUORESCENT MEDIUM WALL PACK

Model #	Wattage	Voltage	Hertz	Ballast	Base	Lumens
JWP2/42CFLMVM-PK	2 X 42W 4-Pin CFL	120-277V	50/60Hz	Electronic	GX24q4	6400

PRODUCT DIMENSIONS

Width	Height	Depth
14-1/2"	9"	7-1/4"

PACKING INFORMATION

Pcs/Ctn	Weight/Ctn	Cube/Ctn
1 pc.	5.4 lbs.	1.10 cft.

APPLICATIONS & FEATURES

APPLICATIONS:

- Ideal for Security and Perimeter Lighting
- For Warehouse, Schools, and Loading Docks
- Commercial, Industrial, and Institutional Lighting

FEATURES:

- Die Cast Aluminum Housing and Hinged Front Frame, 1/2" Coin Plugs with O-Rings for Conduit and Photocell, Textured Architectural Bronze Powder Coat Finish over a Chromate Conversion Coating
- Aluminum Reflector
- Molded Prismatic Borosilicate Glass Lens
- Plug-in Type Socket, GX24Q-4
- Cast-In Template for Mounting Directly over 4" Recessed Outlet Box or Use 1/2" Surface Conduit
- 1 x 42W, 2 x 26W, 2 x 42W
- CSA Listed for Wet Locations

