



## COMPACT FLUORESCENT POLYCARBONATE WALL PACK

Model #	Wattage	Voltage	Hertz	Ballast	Base	Lumens
<b>JWP2/42CFLMVPC-PK</b>	2 X 42W PLT CFL	120-277V	50/60Hz	Electronic	GX24q4	6400

### PRODUCT DIMENSIONS

Width	Height	Depth
14-3/8"	12"	7-1/4"

### PACKING INFORMATION

Pcs/Ctn	Weight/Ctn	Cube/Ctn
1 pc.	9.4 lbs.	0.95 cft.



### APPLICATIONS & FEATURES

#### APPLICATIONS:

- Ideal for Security and Perimeter Lighting
- For Warehouse, Schools, Tunnels and Shopping Complexes
- Commercial, Industrial, and Institutional Lighting

#### FEATURES:

- Precision Die-Cast Aluminum Mounting Plate
- Architectural Bronze Finished
- 1-Piece Vandal Resistant Housing and UV Stabilized Polycarbonate Prismatic Refractor
- Lightweight Fixture (Approx. 7 lbs.)
- Built-In Photocell (Optional)
- UL1598/cUL Listed
- Suitable for Wet Locations
- 1-Year Warranty



**VANDAL RESISTANT**

