



COMPACT FLUORESCENT SMALL WALL PACK

Model #	Wattage	Voltage	Hertz	Ballast	Base	Lumens
JWP42CFLMVPC-PK	1 X 42W 4-Pin CFL	120-277V	50/60Hz	Electronic	GX24q4	3200

PRODUCT DIMENSIONS

Width	Height	Depth
8-1/2"	9-1/2"	7"

PACKING INFORMATION

Pcs/Ctn	Weight/Ctn	Cube/Ctn
1 pc.	3.0 lbs.	0.51 cft.

APPLICATIONS & FEATURES

APPLICATIONS:

- Ideal for Security and Perimeter Lighting
- For Warehouse, Schools, and Loading Docks
- Commercial, Industrial, and Institutional Lighting

FEATURES:

- Die Cast Aluminum Housing, 1/2" Coin Plugs with O-Rings for Conduit and Photocell, Textured Architectural Bronze Powdercoat Finish over a Chromate Conversion Coating
- Aluminum Reflector
- Prismatic Polycarbonate hinged Diffuser with UV Inhibitors and Gasket
- Plug-in Type Socket, GX24Q-4
- Optional Cast Aluminum Mounting Plate Mounts Directly over a 4" Recessed Outlet box or 1/2" surface conduit
- 26, 32 or 42W CFL
- CSA Listed for Wet Locations

